

High Brightness

SQ1H



*Actual Resolution:
3840 x 2160p

• DisplayPort(Ver. 1.2)

- TH-86SQ1H 1200cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-75SQ1H 1500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait

Video Wall

VF2H/ VF2

- TH-55VF2H 700cd/m² 24.7 Operation DIGITAL LINK USB Media Player Post-Portrait 0.88mm AAG Haze 28%
- TH-55VF2 500cd/m² 24.7 Operation DIGITAL LINK USB Media Player Post-Portrait 0.88mm AAG Haze 28%

LFV9



- TH-55LFV9 500cd/m² 24.7 Operation USB Media Player Post-Portrait 3.5mm AAG Haze 28%

Multi-Touch Screen

CQE2-IR



*Actual Resolution:
3840 x 2160p

- TH-86CQE2-IR 400cd/m² 16h Operation USB Media Player Post-Portrait
- TH-75CQE2-IR 400cd/m² 16h Operation USB Media Player Post-Portrait
- TH-65CQE2-IR 500cd/m² 16h Operation USB Media Player Post-Portrait
- TH-55CQE2-IR 500cd/m² 16h Operation USB Media Player Post-Portrait

Standard

SQ2H



*Actual Resolution:
3840 x 2160p
• DisplayPort(Ver. 1.2)
*1: Some functions are limited.
*only applies for 43-65"

- NEW**
- TH-98SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-86SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-75SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-65SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-55SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-50SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
 - TH-43SQ2H 700cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait

SQE2



*Actual Resolution:
3840 x 2160p
• DisplayPort(Ver. 1.2)
*1: Some functions are limited.
*only applies for 43-65"

- TH-98SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-86SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-75SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-65SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-55SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-50SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-43SQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait

EQ2



*Actual Resolution:
3840 x 2160p
*only applies for 43-65"

- TH-86EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait
- TH-75EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait
- TH-65EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait
- TH-55EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait
- TH-50EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait
- TH-43EQ2 500cd/m² 18h Operation USB Media Player 4K Intel Post-Portrait

Entry

CQE2



*Actual Resolution:
3840 x 2160p
*only applies for 43-65"

- TH-98CQE2 500cd/m² 24.7 Operation USB Media Player 4K Intel Post-Portrait
- TH-86CQE2 400cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait
- TH-75CQE2 400cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait
- TH-65CQE2 500cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait
- TH-55CQE2 500cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait
- TH-50CQE2 500cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait
- TH-43CQE2 500cd/m² 16h Operation USB Media Player 4K Intel Post-Portrait

Presentation and collaboration solution

WIRELESS PRESENTATION SYSTEM

For projector and displays



Receiver
(Set-top-box)
Included in TY-WP51 set
and TY-WP5C1

Receiver
(SDM board)
TY-SB01WP

Transmitter
(USB Type-A/HDMI)
TY-WPB1
TY-WP2B1 set

Transmitter
(USB Type-C)
TY-WPBC1
TY-WP2BC1 set

For displays with SDM slot



CONFRENCING SOLUTION



Pitch for wall hanging is VESA compliant

* The availability varies depending on model.

NOTE: The specifications are subject to change without notice.

PressIT

Plug & Play Wireless Presentation System

Dongle based wireless presentation system for fast and simple screen sharing

Lineup



	Basic Set		Receiver (Board)	Transmitter (HDMI/USB)		Transmitter (USB Type-C)	
Model	TY-WPS1	TY-WPSC1	TY-SB01WP	TY-WP2B1	TY-WPB1	TY-WP2BC1	TY-WPBC1
Applicable product	Flat Panel Display / Projector (Panasonic and others)		SQ1/H, SQE2 and EQ2 series	PC/Tablet/Smartphone			
What's included?	1 Receiver (Box) x1 3 Transmitter (HDMI/USB) x2 5 Case for Transmitter x1	1 Receiver (Box) x1 4 Transmitter (USB Type-C) x2 5 Case for Transmitter x1	2 Receiver (Intel® SDM specification) x1	3 Transmitter (HDMI/USB) x2 5 Case for Transmitter x1	3 Transmitter (HDMI/USB) x1	4 Transmitter (USB Type-C) x2 5 Case for Transmitter x1	4 Transmitter (USB Type-C) x1



Connects to any devices*

HDMI-CEC command compatible

Low latency

Antibacterial surface treatment

Presents 4 screens in full HD (supports 4K)**

Lock mode prevents interruptions

Touch back function when used with a interactive display

Seamless video playback with zero lag

* Easy screen sharing with a dedicated app (IOS and Android)
** up to 32 transmitters at once

PressIT360

Providing a more realistic meeting with the 360-degree camera speakerphone



High-quality images from a high-performance 360-degree camera
Four high-performance cameras provide 360-degree immersive images.

360-degree orientation microphone and speaker
Covers a 360-degree radius up to 5m/16.4ft for clear sound collection.

Easy to carry and operate meeting
Video and audio data can be sent to your PC with a single USB-C. Diameter 64 mm, height 285 mm, weight approx. 950 g.