

SOLID SHINE Series

Large-Venue



3-Chip DLP™ Laser light source models
Lens not included with 3-Chip DLP™ models.

	PT-RQ50K	50,000 lm 51,000 lm (Center)	Native 4K ¹	4K ²	4K ³	GeoPro
	PT-RQ35K	30,500 lm 32,000 lm (Center)	4K ²	4K ³	GeoPro	GeoPro
	PT-RZ34K	30,500 lm 32,000 lm (Center)	WUXGA	4K ³	GeoPro	GeoPro
	PT-RQ25K	20,000 lm 21,000 lm (Center)	4K ²	4K ³	GeoPro	GeoPro
	PT-RZ24K	20,000 lm 21,000 lm (Center)	WUXGA	4K ³	GeoPro	GeoPro
	PT-RQ18K	16,000 lm 16,800 lm (Center)	4K ²	4K ³	GeoPro	GeoPro
	PT-RZ17K	16,000 lm 16,800 lm (Center)	WUXGA	4K ³	GeoPro	GeoPro



1-Chip DLP™ Laser light source models
Lens not included with 'L' models.

	PT-REQ15/L	15,000 lm	4K ²	4K ³	GeoPro
	PT-REQ12/L	12,000 lm 12,400 lm (Center)	4K ²	4K ³	GeoPro
	PT-REQ10/L	10,000 lm 10,300 lm (Center)	4K ²	4K ³	GeoPro
	PT-REQ80/L	8,000 lm 8,200 lm (Center)	4K ²	4K ³	GeoPro
	PT-REZ15/L	15,000 lm	WUXGA	4K ³	GeoPro
	PT-REZ12/L	12,000 lm 12,400 lm (Center)	WUXGA	4K ³	GeoPro
	PT-REZ10/L	10,000 lm 10,300 lm (Center)	WUXGA	4K ³	GeoPro
	PT-REZ80/L	8,000 lm 8,200 lm (Center)	WUXGA	4K ³	GeoPro

Installation



1-Chip DLP™ Laser light source models
Lens not included with 'L' models.

	PT-RQ7L	7,500 lm	4K ⁵	4K ⁶	GeoPro
	PT-RQ6L	6,500 lm	4K ⁵	4K ⁶	GeoPro
	PT-RZ7L*	7,500 lm	WUXGA	4K ⁶	GeoPro
	PT-RZ6L*	6,500 lm	WUXGA	4K ⁶	GeoPro
	PT-RZ790/L	7,000 lm 7,200 lm (Center)	WUXGA	4K ⁶	GeoPro
	PT-RZ690/L	6,000 lm 6,200 lm (Center)	WUXGA	4K ⁶	GeoPro



1-Chip DLP™ Laser light source models (Lens fixed)

	PT-FRQ60	6,000 lm 6,200 lm (Center)	4K ⁷	4K ⁸	GeoPro
	PT-FRQ50	5,200 lm 5,400 lm (Center)	4K ⁷	4K ⁸	GeoPro
	PT-FRZ60	6,000 lm 6,200 lm (Center)	WUXGA	4K ⁶	GeoPro
	PT-FRZ50	5,200 lm 5,400 lm (Center)	WUXGA	4K ⁶	GeoPro
	PT-FRZ55*	5,000 lm 5,200 lm (Center)	WUXGA	4K ⁶	GeoPro



LCD Laser light source models

	PT-MZ20KL	20,000 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ17KL	16,500 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ14KL	14,000 lm	WUXGA	4K ⁶	GeoPro
	PT-MZ11KL	11,000 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ882	8,200 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ782	7,500 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ682	6,500 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ880	8,000 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ780	7,000 lm	WUXGA	4K ⁵	GeoPro
	PT-MZ680	6,000 lm	WUXGA	4K ⁵	GeoPro

Portable



LCD Laser light source models (Lens fixed)

	PT-VMZ71*	7,000 lm	WUXGA	4K ⁹	GeoPro
	PT-VMZ61*	6,200 lm	WUXGA	4K ⁹	GeoPro
	PT-VMZ51	5,200 lm	WUXGA	4K ⁹	GeoPro
	PT-VMZ51S	5,200 lm	WUXGA	4K ⁹	GeoPro
	PT-LMZ460	4,600 lm	WUXGA	4K ⁹	GeoPro
	PT-LMZ420	4,200 lm	WUXGA	4K ⁹	GeoPro
	PT-LMW460	4,600 lm	WXGA	4K ⁹	GeoPro
	PT-LMW420	4,200 lm	WXGA	4K ⁹	GeoPro
	PT-LMX460	4,600 lm	XGA	4K ⁹	GeoPro
	PT-LMX420	4,200 lm	XGA	4K ⁹	GeoPro

Short Throw



LCD Laser light source models (Lens fixed)

	PT-TMZ400	4,000 lm	WUXGA	4K ⁹	GeoPro
	PT-TMW380	3,800 lm	WXGA	4K ⁹	GeoPro
	PT-TMX380	3,800 lm	XGA	4K ⁹	GeoPro

Ultra Short Throw



LCD Laser light source models (Lens fixed)

	PT-CMZ50	5,200 lm	WUXGA	4K ⁹	GeoPro
--	-----------------	----------	-------	-----------------	--------

Portable

LCD Lamp based models

	PT-VW360	4,000 lm	WXGA	11
	PT-VX430	4,500 lm	XGA	11
	PT-LW376	3,600 lm	WXGA	11
	PT-LW336	3,100 lm	WXGA	11
	PT-LB426	4,100 lm	XGA	11
	PT-LB356	3,300 lm	XGA	11
	PT-LB306*	3,100 lm	XGA	11

Short Throw

LCD Lamp based models

	PT-TW381R	3,300 lm	WXGA	11
	PT-TW380	3,300 lm	WXGA	11
	PT-TX440*	3,800 lm	XGA	11
	PT-TX350*	3,200 lm	XGA	11

Peripheral

Media Processor

Preliminary Available from CY2024 Q2

	ET-FMP50
	ET-FMP20

Preliminary Available from CY2024 Q4

ET-SBFMP10 SDM type

1: Resolution 4096 x 2160 Pixels. 2: Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON). 3: Available in Japan, US and Canada
4: The availability varies depending on the country. 5: With Smooth Pixel Drive ON.
6: HDMI/DIGITAL LINK input only. 7: Resolution 3840 x 2160 Pixels (With Quad Pixel Drive).
8: HDMI input only. Supports signals up to 4K/30p. 9: HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p.
10: To operate wireless projection, the optional Wireless Module AJ-WM50 is required.
11: To operate wireless projection, the optional Wireless Module ET-WML100 (Stock limited)/AJ-WM50 is required.

*: Available in black/white cabinet.
Ⓢ: The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.

Note: [L] Lens-less model. The specifications are subject to change without notice.
For more information, please visit the website >> panasonic.net/cns/projector/